

AIP-1MDF

1MP CMOS Full HD Vandal-proof Network Mini Dome Camera
1.3 Megapixel CMOS, 30fps @1080P, Lens: 3.6mm
(2.8mm/6mm/8mm optional), PoE, IK10, IP66



- > 1/3" 1.3Megapixel progressive scan Aptina CMOS
 - > H.264 & MJPEG dual-stream encoding
 - > Max 15fps@1.3M(1280×960)&25/30fps@720P(1280×720)
 - > Day/Night, 2DNR, AWB, AGC, BLC
 - > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
 - > 3.6mm fixed lens (2.8mm,6mm,8mm optional)
 - > DC12V, PoE
-

Specification

Camera

Image Sensor: 1/3" 1.3Megapixel Aptina CMOS
Effective Pixels: 1280(H)x960(V)
Scanning System: Progressive
Electronic Shutter Speed: Auto/Manual 1/3~1/10000
Min. Illumination: Color: 0. 1LUX/F1.4
S/N Ratio: >50dB

Camera Features

Day/Night: Auto(Electronic) / Color / B/W

Backlight Compensation: BLC
White Balance: Auto
Gain Control: Auto/Manual
Noise Reduction: 2D
Privacy Masking: Up to 4 areas

Lens

Focal Length: 3.6mm (2.8mm, 6mm, 8mm optional)
Max Aperture: F1.8 (F.20/F1.8/F1.6)
Angle of View: H: 70° (114°/46°/35°)
Mount Type: Board-in Type

Video

Compression: H.264 / MJPEG
Resolution: 1.3M(1280×960) / 720P(1280×720) / D1(704×480) / CIF(352×240)
Frame Rate:: Main Stream: 1.3M(1~15fps)/720P(1 ~ 25/30fps)
 Sub Stream: D1/CIF(1 ~ 25/30fps)
Bit Rate:: H.264: 32K ~ 8192Kbps
 MJPEG: 32K ~ 12288Kbps

Network

Ethernet: RJ-45 (10/100Base-T)
Protocol: IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF: ONVIF Ver. 2.0
Max. User Access: 10 users
Smart Phone: iPhone, iPad, Android, Windows Phone

General

Power Supply: DC12V, PoE(802.3af)
Power Consumption: <1.5W
Working Environment: -10°C~+60°C, 10%~90%
Dimensions: Φ110×54mm
Weight: 0.25kg

*Above specifications and design subject to change without notification

Dimensions (mm)

