

AIP-2MBV9

2 Megapixel Full HD Network IR-Bullet Camera with Motorized Varifocal Lens



- 1/3" 2 Megapixel progressive scan Exmor CMOS
- H.264 & MJPEG dual-stream encoding
- 30fps@1080P(1920×1080)
- DWDR, Day/Night(ICR), 2DNR, AWB, AGC, BLC, auto iris
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 3~9mm motorized varifocal lens
- Max. IR LEDs Length 30m
- IP66, PoE

Specifications

Image Sensor: 1/3" 2 Megapixel Exmor CMOS
Effective Pixels: 1920(H)x1080(V)
Scanning System: Progressive
Electronic Shutter Speed: Auto/Manual, 1/4~1/10000s
Min. Illumination:: color: 0.1 Lux/F1.2, B/W: 0.01Lux/F1.2; 0Lux/F1.2(IR on)
S/N Ratio: >50dB
Video Output: 1 channel, BNC(1.0Vp-p/75Ω)
Max. IR LEDs Length: 20m

Day/Night: Auto(ICR)/Color/B/W
Backlight Compensation: BLC / HLC / DWDR
White Balance: Auto
Gain Control: Auto/Manual
Noise Reduction: 2D
Privacy Masking: Up to 4 areas
Focal Length: 3~9mm motorized
Max Aperture: F1.2
Focus Control: auto
Angle of View: H: 105°(Wide) ~ 36°(Tele)
Lens Type: Motorized / Auto Iris (DC)
Lens Mount Type: Board-in type
Video Compression: H.264 / MJPEG
Video Resolution: 1080P(1920×1080) / 720P(1280×720) / D1(704×480) / CIF(352×240)
Main Stream Image Frame Rate: 1080P / 720P (1~30fps)
Sub Stream Image Frame Rate: D1/CIF(1 ~ 30fps)
Audio Compression: G.711a / G.711u(64kbps) / PCM(128kbps)
Audio Interface: 1/1 channel In/Out
Ethernet: RJ-45 (10/100Base-T)
Network Functions: IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF: Ver. 2.0
Max. User Access: 10
Smartphone: iPhone, iPad, Android, Windows Phone
Memory Slot: Micro SD, Max 32GB
Power Supply: DC12V(AC24 optional), PoE(802.3af)
Power Consumption: 10W
Working Environment: -10°C~+60°C, 10%~90%
Ingress Protection: IP66
Dimensions: φ104mm × 306.7mm

*Above specifications and appearance of product subject to change without notice

Dimensions

