

MINI SPEED DOME CAMERA DMS-200



100X ZOOM
TDN, DNR


FEATURES

- 410 K, 1/4" Interline Transfer Sony CCD
- 10x Optical zoom lens, Auto focus, Auto iris and Zoom tracking (Total Zoom x100)
- Horizontal resolution of 520 TVL at color mode and 570 TVL at B/W mode
- Day & Night (ICR), Digital noise reduction (DNR), Smart zoom
- 250 Preset Positions, Swing, Group, Spiral, Auto Flip, Alarm
- Privacy Zone Masking (4 Zones),

SPECIFICATIONS

| MODEL | DMS-200 | |
|-----------------------|---|-----------------|
| Signal system | NTSC | PAL |
| Image sensor | 1/4" Sony Super HAD CCD | |
| Effective pixels | 768(H) × 494(V) | 752(H) × 582(V) |
| Horizontal resolution | More than 520 TVL, B/W 570 TVL | |
| Lens | 10x Optical zoom, f=3.8-38mm, F 1.8 | |
| Digital zoom | 10x (Total zoom 100x) | |
| Angle of view | Approx 51.2° (Wide), Approx 5.58° (Tele), | |
| Minimum illumination | 0.7 Lux, 0.0007Lux(D&N), 50IRE | |
| Luminance S/N ratio | More than 50dB | |
| Video output | 1 Vp-p Composite video output 75Ω | |
| Focus mode | Auto / Manual / Oneshot | |
| SSNR | Off / Low / Middle / High | |
| Back Light | Off / Low / Middle / High | |
| Shutter speed | Auto / 1/128 ~ 1/120,000 sec | |
| Sharpness control | Level (0-10) | |
| Motion Detection | On/Off | |
| Alarm in/out | 4 Inputs / 1 Relay Output | |
| Pan/Tilt angle | 360° Endless / 92° | |
| Pan speed | 0.1° ~ 240°/sec (64 Levels) | |
| Preset point | 250 Presets | |
| Preset Speed | Max 360°/sec (64 Levels) | |
| Privacy zones masking | 4 Zones | |
| Operating temperature | -10°C ~ 50°C (-14°F ~ 122°F) | |
| Communication system | RS-485 / 422 | |
| OSD | Built-in | |
| Operating humidity | Less than 90%RH | |
| Dimensions | 104(Diameter)mm × 138(Height)mm | |
| Weight | About 0.5Kg | |
| Construction | PC body, Clear vandal bubble (PC) | |
| Power consumption | 5W | |
| Power supply | AC24V, 50/60Hz | |

DIMENSIONS



(UNIT : mm)