DSC-300SE5 OUTDOOR PTZ DOME CAMERA

- ✓ 1/4" Sony Double Density Interline CCD
- ✓ Hitachi Zoom Camera Module
- ✓ 35x optical zoom with 12x digital magnifier (444x total zoom)
- ✓ Open shutter to capture images in very low light
- ✓ Supports RS-485 & RS-422



Image sensor	1/4" Sony Double Density Interline CCD
Number of total pixels	811(H)X508(V) 410K
Number of effective pixels	768(H)X494(V) 380K
Horizontal resolution	More than 550 TV Lines
Lens	35x Optical zoom, f=3.5 ~ 129.5mm
Digital zoom	12x (Total zoom: 444x)
Horizontal Angle of View	H: 55.5~1.59°, V: 42.5~1.19°
Minimum Illumination	Normal Mode: 0.7 Lux Digital Slow Shutter Mode: 0.0001 Lux / F1.6 Day & Night Mode: 0.1 Lux
Luminance S/N Ratio	More than 50dB
OSD	On/Off
Video Output	1 Vp-p Composite video output 75 ohm terminated
SSNR	Off, Low, Middle, High
Focus Mode	Auto/Manual/One-shot
WDR	On/Off
Sharpness Control	Level 0~10
Stabilizer	On/Off
Shutter Speed Control	1/120 - 1/60,000 Sec
Alarm In/Out	4 Input / 1 Relay Out
Pan/Tilt Angle	360° Endless / 92°
Pan speed	Manual: 0.1°-240°/sec (64 levels), Preset: Max 360°/sec (64 levels)
Privacy Zone Masking	16 Zones
Communication System	RS-485 / 422
Preset Point	250 Presets
Environment	Outdoor
Operating Temperature	-40°C to 50°C (-40°F to 122°F)
Operating Humidity	Less than 90%RH
Dimensions	8.7(ø) x 11.6(H) Inch
Weight	About 11.4 LBS
Construction	Ivory body (ABS), Black bubble (ABS)
Power consumption	21W (Max)
Power supply	AC24V 60/50 Hz
bove specifications and design	n subject to change without notification