

HD-2BX

2.1 megapixel HD-SDI camera, Box type, 1/3" CMOS Sensor



Main Features:

- 1/3" 2.1Megapixel CMOS Sensor
- 1080(1920x1080)@30fps
- High resolution digital zoom (x64)
- PIP(Full Image / Zoom Image)
- Privacy Zone
- OSD (On Screen Display)
- DNR (Digital Noise Reduction, 2D+3D)
- HLC (High Light Compensation)
- HD-SDI/CVBS Output
- DC Auto Iris , MANUAL Lens
- Built in RS-485 Port
- DC12V

*Lens not included

Specification:

Image Sensor	1/3" 2.1Megapixel CMOS
Total Pixels	2010(H)x1108(V) (2,227,080 Pixels)
Active Pixels	1944(H)x1092(V) (2,122,848 Pixels)
Scanning System	Progressive
Resolution	Digital : 1920x1080p(1080p/30fps), 1280x720p(720p/60fps)
Min. Illumination	0.02 Lux (Sens-up x60)
S/N Ratio	more than 50dB (AGC off)
White Balance	ATW / AWC / Manual
Video Output	HD SDI / CVBS : 1.0Vp-p (75Ω)
Shutter speed	Auto / Manual Selectable
OSD	Built-in
BLC	BLC / HSBL / OFF Selectable
AGC	High / Middle / Low
DNR	2 DNR / 3 DNR
Day & Night	Auto / BW / Color
Defog	High / Middle / Low / Off
PIP / D-Zoom	On(x2~x64)
Privacy	On(8 Zone) / Off
Power Supply	DC 12V ± 10%
Operating temperature	-10°C~+50°C
Operating Humidity	0~90% RH