

## HDC-B22811-2

2.1 megapixel HD-SDI camera, Box type, 1/3" CMOS Sensor



### Main Features:

- 1/3" 2.1 Megapixel CMOS Sensor
- 1080(1920x1080)@30fps
- High resolution digital zoom (x64)
- PIP(Full Image / Zoom Image)
- Privacy Zone
- OSD (On Screen Display)
- DNR (Digital Noise Reduction, 2D+3D)
- HLC (High Light Compensation)
- HD-SDI/CVBS Output
- 2.8~11mm / F1.2 Varifocal ICR Lens
- Built in 36 IR LEDs
- DC12V

**Specification:**

|                              |                                                             |
|------------------------------|-------------------------------------------------------------|
| <b>Image Sensor</b>          | 1/3" 2.1 Megapixel CMOS                                     |
| <b>Total Pixels</b>          | 2010(H)x1108(V) (2,227,080 Pixels)                          |
| <b>Active Pixels</b>         | 1944(H)x1092(V) (2,122,848 Pixels)                          |
| <b>Scanning System</b>       | Progressive                                                 |
| <b>Resolution</b>            | Digital : 1920x1080p(1080p/30fps),<br>1280x720p(720p/60fps) |
| <b>Min. Illumination</b>     | 0.02 Lux (Sens-up x60)                                      |
| <b>S/N Ratio</b>             | more than 50dB (AGC off)                                    |
| <b>White Balance</b>         | ATW / AWC / Manual                                          |
| <b>Video Output</b>          | HD SDI / CVBS : 1.0Vp-p (75Ω)                               |
| <b>Shutter speed</b>         | Auto / Manual Selectable                                    |
| <b>OSD</b>                   | Built-in                                                    |
| <b>BLC</b>                   | BLC / HSBLC / OFF Selectable                                |
| <b>AGC</b>                   | High / Middle / Low                                         |
| <b>DNR</b>                   | 2 DNR / 3 DNR                                               |
| <b>Day &amp; Night</b>       | Auto / BW / Color                                           |
| <b>Defog</b>                 | High / Middle / Low / Off                                   |
| <b>PIP / D-Zoom</b>          | On(x2~x64)                                                  |
| <b>Privacy</b>               | On(8 Zone) / Off                                            |
| <b>Power Supply</b>          | DC 12V ± 10%                                                |
| <b>Operating temperature</b> | -10°C~+50°C                                                 |
| <b>Operating Humidity</b>    | 0~90% RH                                                    |