

IPC-HDW1300S

3 Megapixel Full HD Network Mini IR Dome Camera



- 1/3" 3 Megapixel progressive scan CMOS
- H.264 & MJPEG dual-stream encoding
- Max 15fps @3.0M(2048×1536) & 30fps @1080P(1920×1080)
- DWDR, Day/Night(ICR), AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 3.6mm fixed Lens
- Max. IR LEDs length 98ft
- IP66, PoE

Specifications

Camera

Image Sensor: 1/3" 3 Megapixel progressive scan CMOS

Effective Pixels: 2048(H)x1536(V)

Scanning System: Progressive

Electronic Shutter Speed: Auto/Manual, 1/4~1/10000s

Min. Illumination: 0.1Lux/F1.6 (Color), 0 Lux/F1.2(IR on)

S/N Ratio: More than 50dB

Camera Features

Max. IR LEDs Length: 98ft
Day/Night: Auto(ICR) / Color / B/W
Backlight Compensation: BLC / HLC / DWDR
White Balance: Auto / manual
Gain Control: Auto / Manual
Noise Reduction: 2D
Privacy Masking: Up to 4 areas

Lens

Focal Length: 3.6mm
Max Aperture: F1.6
Focus Control: Manual
Angle of View: H: 71.9°
Lens Type: Fixed lens
Mount Type: Board-in Type

Video

Compression: H.264H / H.264B / H.264 / MJPEG
Resolution: 15fps in 3M(2048×1536) / 1080P(1920×1080) / 720P(1280×720) / D1(704×480) / CIF(352×240)
Frame Rate: Main Stream 1080P / 720P(1 ~ 30fps), Sub Stream D1 / CIF(1 ~ 30fps)
Bit Rate: H.264, 16K ~ 8192Kbps

Network

Ethernet: RJ-45 (10/100 Base-T)
Protocol: IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS
Compatibility: ONVIF, CGI
Max. User Access: 20 users
Smart Phone: iPhone, iPad, Android, Windows Phone

General

Power Supply: DC12V, PoE(802.3af)
Power Consumption: Less than 5W
Working Environment: -30°C~+60°C, less than 95% RH
Ingress Protection: IP66
Dimensions: Φ4.5 × 3.4 inch
Weight: 0.9 lbs

*Above specifications and appearance of product subject to change without notice
