

Portable Surveillance



Portable Wireless PTZ Camera System

The Portable Wireless Pan-Tilt-Zoom (PTZ) Camera System is up and operational within minutes. No wires to connect. Just deploy the system into the area of operation and turn it on. This Rapid Deployment Kit (RDK) Portable Wireless PTZ Camera System and dozens more like it will create an instant surveillance perimeter for you and your team. This will provide you with a virtual fence of PTZ cameras that can be wirelessly monitored/recorded using our [V4-Pro Portable Surveillance System](#) or used in "Stand Alone" Mode allowing multiple users to control the portable PTZ camera using a laptop, PDA or in-vehicle computer.

MORE INFO

[Click here](#) to watch a video of the system.

Portable Wireless PTZ Camera System

The portable wireless PTZ camera can be tripod-mounted (or other structure) and operates on both 2.4Ghz & 5.8Ghz for the longest signal distance. This RDK is designed for fast, short missions or a long term deployment with electric or battery power options. The portable PTZ camera has a powerful 35x optical zoom and night time optics that are capable of reading license plates and identifying targets from hundreds of yards away. Within seconds of receiving power, the portable wireless PTZ camera automatically begins transmitting security video feeds to you.

Durable & Easy. The portable wireless PTZ is able to withstand the stress of fierce weather and careless handling. The PTZ dome has a vandal resistant, poly-carbonate bubble and aluminum steel construction. It is weather resistant, with an IP63 rating (or higher depending on ventilation requirements). Our smart power system allows for seamless, uninterrupted transfer between power sources.

Rapid Deployment. AT AVP Security, our outdoor PTZ camera is able to be deployed in minutes, read license plates, and continue to identify threats/targets from hundreds of yards away. Our portable wireless PTZ has a 35x zoom and 570 lines resolution. The portable PTZ camera comes with a rugged, quick release tripod mount that allows for easy setup with no tools necessary. We also include a high-wind tie down kit with connection points integrated into the camera mount, cam buckle straps, spiral ground stakes (for silent anchoring), and carry bag.

(Dome Housing and Support Arm available in BLACK or WHITE.)

Contact us today for a customized quote.

The U.S. Military, U.S. Dept. of Homeland Security, U.S. Dept of State, NATO, and various Law Enforcement Agencies have placed their trust in AVP Security Systems.

Once you utilize our systems in *your* operations, you'll see why!

Hardware Specifications

Portable Wireless PTZ Camera System

(Continued)

- ⊗ 1/4" interline transfer CCD (SONY) with DSP 7
- ⊗ 35x optical zoom with 12x digital magnifier.(420x total zoom)
- ⊗ Day & Night Vision (0.0001 Lux in DSS Mode)
- ⊗ Programmable presets, group-tour, auto-tour, trace PTZ (pattern) 250 presets
- ⊗ Auto flips and Automatic Gain Control, line-lock and white balance. (user-selectable on/off)
- ⊗ Temperature-controlled interior environment
- ⊗ Vandal resistant bubble (Poly-carbonate) and aluminum steel construction
- ⊗ Weather Resistant - (IP63 Rating) - (or higher depending on ventilation requirements)
- ⊗ External Connections - Antenna Type -N Female, 120/230 Vac Input
- ⊗ Locking Mechanism - 7 Heavy-Duty latching clasp seal the case tightly shut. There are 2 attached reinforced inserts for mechanical locks
- ⊗ Transportation - Retractable tote handle, 4 Heavy-duty castors and 3 heavy-duty side handles make transporting this unit very easy
- ⊗ Tripod Mount: 6' double telescoping pole. (Includes tie-down kit for high wind conditions)
- ⊗ Wireless Radio: 600mw RF output power for greater range, 2.4 GHz & 5.8 GHz wireless 128/256bit Encryption includes internal 13dbi directional antenna with color-coded signal strength LED lights (Modes: Client, AP, Repeater)
- ⊗ Multi-input smart power system (automatic) with an internal battery that will power the system for about 5-10 hours. External battery can be connected for extended operating time. System automatically detects input power, charges battery, and seamlessly switches between all power sources without operator intervention. External power sources include: Vac 115 or 230 volts, Vdc 12 to 30. The internal battery automatically operates as a back-up UPS in the event of an external power failure
- ⊗ AC Power Input: Accepts 115/230 Vac (automatic switching)
- ⊗ Operating Temperature: 0'f - 125'f
- ⊗ Transport Case Overall Dimensions: 30.5" L x 18.5" W x 11.50" H
- ⊗ Weight: 69 LBS (w/ camera, transmitter, tripod, transport case, tie-down kit, and internal batteries)

