

SWT-8US
8 Port PoE Ethernet Switch
SFP Optical Uplink Port



This switch is an unmanaged POE switch. It has one uplink ethernet port nad one optical port 1000Mbps; 8 100Mbps POE ethernet ports support af/at standard. This product is designed for HD IP camera with POE. It makes powering thses devices that are far away from the power source easy. This product offers an optical port to connect to a long distant network via fiber optic. The uplink ethernet port offers 1000Mbps speed that can run up to 150m, transmitting up to 1M package data cache. It supports IEEE802.3x full duplex flow control, auto MDI/MDIX function.

Specifications

Power Adapter Voltage: DC 48V-57V

Power Consumption: Default af standard < 120W, at standard < 240W (purchase power adapter)

Network Port

1~8 port: 10/100Mbps PoE network port

UPLINK port:10/100/1000Mbps network port

SFP:1000Mbps optical fiber SFP module port

Network Transmission Distance

1~8 port:150m

UPLINK port: 150m

SFP: Depends on the optical module transmission performance

Network Transmission Medium: Cat5/5e/6 standard network cable

PoE Protocol: IEEE802.3 af/at

PoE Power Supply: End-span

PoE Power Consumption: af=15.4W (every port), at=30W (every port)

Network Standard

IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3ab 1000BASE-TX;

IEEE802.3z 1000-SX/LX;

IEEE802.3 X

Switch way: Store and forward

Package data cache: 1M

MAC address list: 8K

Power indicator: 1 LED (red)

Optical port LED indicator: 1 SPF port indicator (green)

Uplink network port LED indicator: 1 (green on the RJ 45 socket)

PoE network LED indicator: 8 PoE status indicator (yellow on the RJ 45 socket)

8 network status indicator (green)

PoE Reset Button: 8, corresponding with 1~8 port

Reset Button: 1, switch restart

Communication port lightning protection: 4KV per: IEC61000-4-5

ESD protection: 1a contact discharge 3 level

1b air discharge 3 level

Per:IEC61000-4-2

Working temperature: -40 ~ 55C

Storage temperature: -40 ~ 70C

Humidity (non-condensing): 0~95%

Dimension (L×W×H): 159mm × 110mm × 46.5mm

Material: Aluminum

Color: Black


Weight: 570g

MTBF: >30000h


*Above specifications and appearance of product subject to change without notification

Certification






Back



Up



Application

